

GAS CAPACITY CHART

Balloon Type	Inflated Diameter		Lift Ability	Gas Capacity		Average Flying Time*
	Inches	Centimeter		M ³	Liter	
R-5	5"	13 cm	---	---	---	---
R-9	9"	23 cm	6 g.	0,007 m ³	7 l.	10 - 14 h.
R-10	10"	25 cm	6 g.	0,008 m ³	8 l.	12 - 16 h.
R-12	12"	30 cm	10 g.	0,015 m ³	15 l.	18 - 24 h.
R-18	18"	45 cm	51 g.	0,056 m ³	56 l.	36 h.
R-24	24"	60 cm	90 g.	0,110 m ³	110 l.	2 d.
R-36	36"	91,5 cm	184 g.	0,226 m ³	226 l.	3 - 5 d.
Stuff	18"	45 cm	51 g.	0,056 m ³	56 l.	36 h.
HRT-6	6"	15 cm	---	---	---	---
HRT-12	12"	29 cm	3 g.	0,009 m ³	9 l.	14 h.
LOL-6	6"	15 cm	---	---	---	---
LOL-12	12"	29 cm	8 g.	0,015 m ³	15 l.	18 h.
LOL-660	6" x 60"	15 x 150 cm				10 h.
160	1" x 60"	2,5 x 150 cm	---	---	---	---
260	2" x 60"	5 x 150 cm	---	---	---	---
360	3" x 60"	7,6 x 150 cm	---	---	---	---

The listed average inflation sizes, lift ability and flying time are a conservative average.

The use of ULTRA HI-FLOAT™ is recommended for all helium-filled latex balloons.
ULTRA HI-FLOAT™ can increase the flying time of latex balloons up to 25 times.

**Actual flying times vary depending on temperature and atmospheric conditions.*

